



INNOVATIONEN MIT PROFIL

DECLARATION OF PERFORMANCE

pursuant to Annex III of Regulation (EU) No. 305/2011 amended by Delegated Regulation (EC) No. 574/2014
(Construction Products Regulation)

for the Schlüter®-DITRA-HEAT waterproofing system

no. DoP-003

Unique identification code of the product-type:

Schlüter®-DITRA-HEAT, -KERDI-KEBA, -KERDI-KERECKFI&FA, -KERDI-FIX, -BARA-HV, -KERDI-COLL-L, -KERDI-KM

Intended use(s):

Waterproofing system against water on walls and floors in interior spaces.

Manufacturer:

Schlüter-Systems KG
Schmölestraße 7
DE-58640 Iserlohn, Germany
Tel: +49 2371 971 0
Web: www.schlueter-systems.com

Authorised representative:

Not applicable

System(s) of assessment and verification of constancy of performance:

System 2+
System 3 (Reaction to fire)

European Assessment Document:

EAD 030436-00-0503

European Technical Assessment:

ETA-15/0050:2023

Technical Assessment Body:

ETA-Danmark A/S

Notified body/bodies:

Säurefließner-Vereinigung e. V. (NB 1212)
MPA Dresden GmbH (fire behaviour) (NB 0767)

Declared performance/s:

Characteristic	Assessment of the characteristic		System of assessment and verification of constancy of performance	Harmonised technical specification
Safety in case of fire (BWR2)			3	EAD 031436-00-0503
Reaction to fire EN 13501-1	Euro class E			
Hygiene, health and the environment (BWR3)				
Content, emissions and/or assessment of release of dangerous substances				
Release scenario: IA2	after 3 days [$\mu\text{g}/\text{m}^3$]	after 28 days [$\mu\text{g}/\text{m}^3$]		
SVOC	none	none		
TSVOC	<5	<5		
Water vapour permeability	$\mu = 72100/\text{Sd} = 124.2 \text{ m}$			
Water tightness	Waterproofing			
Crack bridging ability	Assessment Category 3			
Bonding strength	Assessment Category 1			
Scratching resistance	Not applicable			
Joint bridging ability	Approved			
Water tightness in the area of penetrations	Waterproofing			
Dimensional stability	Longitudinal direction (MD): $\Delta\text{L} = +0.1\%$			
	Transverse direction (CMD): $\Delta\text{L} = -0.2\%$			
Resistance to temperature	Approved			
Resistance to water	Assessment Category 1 $\geq 0.2 \text{ Mpa}$			
Resistance to alkalinity	Assessment Category 2 $\geq 0.2 \text{ Mpa}$			
Resistance to mechanical sealing	Not applicable			
Flexibility	No cracks or other surface damage			
Safety and accessibility in use (BWR4)				
Slipperiness	Not applicable			
Cleanability	Not applicable			
Thickness	5.5 ± 1 mm			

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Marc Schlüter, Managing Director
[name and function]

Iserlohn, March 17, 2025
[place and date of issue]


[signature]