


2.8 Schluter®-SCHIENE-STEP

H = mm - po.	Numéro d'article				
	Acier inoxydable brossé 304 (1.4301 = V2A) (EB)				
	Profilé	Coin interne, 90°	Coin interne, 135°	Coin externe, 90° et capuchon de fermeture	Coin externe, 135°
A: 39 mm - 1-1/2"					
6 - 1/4	SS 60 EB 39	I90 / SS 60 EB 39	I135 / SS 60 EB 39	E90 / SS 60 EB 39	E135 / SS 60 EB 39
9 - 11/32	SS 90 EB 39	I90 / SS 90 EB 39	I135 / SS 90 EB 39	E90 / SS 90 EB 39	E135 / SS 90 EB 39
11 - 7/16	SS 110 EB 39	I90 / SS 110 EB 39	I135 / SS 110 EB 39	E90 / SS 110 EB 39	E135 / SS 110 EB 39
12.5 - 1/2	SS 125 EB 39	I90 / SS 125 EB 39	I135 / SS 125 EB 39	E90 / SS 125 EB 39	E135 / SS 125 EB 39
A: 30 mm - 1-3/16"					
9 - 11/32	SS 90 EB 30	-	-	E90 / SS 90 EB 30	-
11 - 7/16	SS 110 EB 30	-	-	E90 / SS 110 EB 30	-
12.5 - 1/2	SS 125 EB 30	-	-	E90 / SS 125 EB 30	-
A: 11 mm - 7/16"					
6 - 1/4	SS 60 EB 11				
12.5 - 1/2	SS 125 EB 11				

H = mm - <i>po.</i>	Numéro d'article	
	Acier inoxydable brossé 304 (1.4301 = V2A) (EB)	
	Raccord	
A: 39 mm - 1-1/2"		
6 - 1/4	V / SS 60 EB 30	
9 11/32	V / SS 90 EB 39	
11 - 7/16	V / SS 110 EB 39	
12.5 - 1/2	V / SS 125 EB 39	
A: 30 mm - 1-3/16"		
9 11/32	V / SS 90 EB 30	
11 - 7/16	V / SS 110 EB 30	
12.5 - 1/2	V / SS 125 EB 30	
A: 11 mm - 7/16"		
6 - 1/4	V / SS 60 EB 11	
12.5 - 1/2	V / SS 125 EB 11	

Longueur : 8' 2-1/2" — 2.50 m



2.8 Schluter®-SCHIENE-STEP

H = mm - po.	Numéro d'article	
	Aluminium anodisé mat (AE)	Aluminium nickel anodisé mat (AT)
A: 30 mm - 1-3/16"		
8 - 5/16	SS 80 AE 30	SS 80 AT 30
10 - 3/8	SS 100 AE 30	SS 100 AT 30
12.5 - 1/2	SS 125 AE 30	SS 125 AT 30
15 - 9/16	SS 150 AE 30	SS 150 AT 30
A: 39 mm - 1-1/2"		
8 - 5/16	SS 80 AE 39	SS 80 AT 39
10 - 3/8	SS 100 AE 39	SS 100 AT 39
12.5 - 1/2	SS 125 AE 39	SS 125 AT 39
15 - 9/16	SS 150 AE 39	SS 150 AT 39

Longueur : 8' 2-1/2" — 2.5 m